



2016 PETALUMA SPEEDWAY **WINGLESS SPRINTS RULES**

Current as of February 10, 2016

PETALUMA SPEEDWAY

2016 Wingless Sprint Car Rules

As of 2-10-2015

Table of Contents

1	Safety Equipment	2
2	Weight.....	4
3	Chassis	4
4	Bumpers, Nerf Bars & Rub Rails	5
5	Engine	5
6	Drivetrain.....	6
7	Exhaust	7
8	Body.....	7
9	Fuel System	8
10	Tires and Wheels.....	8
11	Miscellaneous Class Specific Rules	8
12	Disclaimer	8

Changes are highlighted in Yellow.

1 Safety Equipment

1.1 Driver

Driver Suit

Drivers suit. Must be free of defects, rips, or tears. Must be SFI approved 3.2/1 or 3.2/5. If you choose to use the SFI 3.2/1 single layer suit you must wear Nomex underwear. Suits may be one or two piece.

Any popular approved type, for example, Simpson, Nomea, etc., any color is allowed. All drivers at all times must wear approved fire suits. For example, testing, hot lapping, running on the track and racing.

Fire proof uniform gloves and shoes are mandatory. SF13.2N1 rating minimum.

Head socks or skirts mandatory.

Helmet

Helmet. Must use a Snell SA2010 or newer helmet. No "S" or "M" helmets allowed. All helmets must have a "SA" sticker with the date and serial number. Helmets with a altered, missing or un-readable "SA" sticker will not be allowed.

Driver's helmet should carry name, blood type, allergies and date of last tetanus shot along with pertinent medical history – this is optional, but suggested.

Other

Gloves. Must be SFI 3.3/1. Must be free of defects and cover the complete hand.

Neck Brace. Must be a SFI 3.3/1 minimum. It is highly recommended that you utilize a head and neck restraint system.

Shoes. Must be SFI 3.3/5. Must be free of defects

Arm restraints are mandatory.

Helmet restraint, neck collar mandatory.

PETALUMA SPEEDWAY

2016 Wingless Sprint Car Rules

1.2 Driver Compartment

Roll cage padding required. Knee pads and guards required.

Quick release steering wheel mandatory.

All accelerators must be equipped with safety toe strap and proper return springs.

Window Net

Window Net. Must use a SFI 27.1. Nets must not be older than two years old. Nets missing tags, date not punched out, or un-readable tags will not be allowed.

1.3 Fire Equipment

Car

Pit

Each pit area must be equipped with a serviceable A-B-C type (dry powder) fire extinguisher minimum 7.5 pound capacity. This is in addition to extinguisher in race car. The extinguisher must be visible from pit road.

1.4 Seat

Seat must be mounted to the centerline of the chassis.

Racing seats ONLY. High back recommended.

Headrest must be high impact and energy absorbing

Seat must be mounted in 4 places to the chassis with minimum 3/8" steel bolt and nut.

Mounting hole in seat must have a 2" diameter mounting plate with a minimum .060"

1.5 Seat Belts

Seat Belts

5 point hook-up with 3" belts minimum.

Safety Belts. Must be SFI 16.1. Belts must not be older than two years old. Belts with missing tags, date not punched out, or un-readable tag will not be allowed.

Shoulder straps or harness and safety belts are mandatory and shall be worn at all times when on track.

Safety belts must be fastened behind the seat and at least 6" or lower below the shoulder and sub-marine belt. Belts to mount on roll cage.

1.6 Communication

Raceceiver and transponders are mandatory and are available to rent or buy at track.

No 2 way radios, scanners, cell phones or Nextel allowed. Radios will be confiscated.

1.7 Miscellaneous

ALL SAFETY ITEMS WILL BE DESIGNED AND INSTALLED TO THE SATISFACTION OF THE TECHNICAL INSPETOR (EXCEPTION WILL BE MADE IN THE AREA OF SAFETY. ANY ADJUSTMENTS OR ALTERATIONS SUGGESTED BY OFFICIALS WILL BE IMMEDIATELY ENFORCED. YOU HAVE NO RECOURSE.

A medical examination of all drivers may be required as needed by officials.

All wrecked cars must be inspected by a safety official before re-entering competition. A race car may be inspected by officials at any time.

PETALUMA SPEEDWAY

2016 Wingless Sprint Car Rules

Any car found to be illegal will be disqualified from competition.

ANY CAR, TEAM, OR DRIVER NOT MEETING SPEEDWAY SPECIFICATIONS, OR STANDARD RACING SAFETY AND EQUIPMENT, IS SUBJECT TO AUTOMATIC DISQUALIFICATION AND/OR PENALTIES.

2 Weight

2.1 Class Weight Rules

All cars must weigh 1650 lbs. with driver and all driver's equipment.

You can be weighed at any time during the night.

2.2 Add-On Weight

3 Chassis

3.1 Eligible Models

Open to any sprint car chassis 1984 to present.

3.2 Dimensions/Wheel Base

Wheelbase minimum of 82".

Wheel base maximum of 96".

3.3 Frame Specifications

Motor, body, seat and fuel tank must be mounted to the centerline of the chassis.

3.4 Roll Cage Specifications

Minimum cage structure to be no less than 1 3/8" 0.0. with .095 minimum wall thickness. Cage MUST extend 2" above driver's helmet. A halo bar will be required if drivers helmet sits too high.

NO TITANIUM. NO EXCEPTIONS.

3.5 Driver's Compartment

3.6 Steering

3.7 Front Suspension

Any conventional torsion bar or coil-over suspension is allowed. Combining the two is allowed.

Straight front axle only.

NO COCKPIT ADJUSTABLE SUSPENSION DEVICES. NO EXCEPTIONS.

All moly or hiem ball joints will have flat washers installed.

3.8 Front Springs

3.9 Rear Suspension

Any conventional torsion bar or coil-over suspension is allowed. Combining the two is allowed.

No independent rear suspension allowed.

NO COCKPIT ADJUSTABLE SUSPENSION DEVICES. NO EXCEPTIONS.

PETALUMA SPEEDWAY
2016 Wingless Sprint Car Rules

3.10 Rear Springs

3.11 Shocks

One shock per wheel.

3.12 Brakes

Minimum left front and left inboard rear brake system.

Front and rear brakes must work at start of event. Rear must work at ALL times.

Additional right rear brake OK.

Steel, cast iron or aluminum rotors only. No titanium.

3.13 Electrical and Electronics

Battery

Must carry 12 volt battery. Recommended location: under driver's seat.

If battery is WET TYPE, must be covered to prevent acid spills.

Electrical

Electronics

3.14 Engine Compartment

3.15 Engine Location

Motor must be mounted to the centerline of the chassis.

4 Bumpers, Nerf Bars & Rub Rails

Bumpers and nerf bars must be sprint car type bars and securely bolted to the chassis with minimum 1/4" bolt.

Bumpers and nerf bars will be constructed of no less than 1" 0.0. and .60 wall thickness.

Side nerf bars may have triangular or 4 point configuration and may not extend outside rear tires.

5 Engine

5.1 Block

360 cu. in. MAXIMUM. NO EXCEPTIONS.

Cast iron block and heads required. Stock valve angle (23 degrees for Chevy).

5.2 Crankshaft

5.3 Connecting Rods

5.4 Pistons

5.5 Heads

5.6 Springs

5.7 Valves

5.8 Camshaft

Flat tappet cams only.

PETALUMA SPEEDWAY
2016 Wingless Sprint Car Rules

5.9 Rockers

Roller rockers and girdles OK.

5.10 Oil Pan

Gear drive and dry sump oil systems OK.

5.11 Intake

Aluminum 4bbl. intake manifold OK. 1/2" pipe plug in valley area of the intake manifold, (between carb. and check cams with opening engines.

5.12 Air Cleaner

5.13 Fuel Delivery System

Holley #4412 or Demon or 9647 Series 500 cfm. 2bbl. carburetor. Track Go-No Go Gauge will monitor carb. Specifications.

1 11/16" throttle bore; shafts and throttle plates must be stock. Choke tower may be removed. External jets C THREE METAL throttle return springs MANDATORY.

Venturi may be opened .010 over catalog specs.

Bottom of carburetor may be no more than 4" from top of manifold. No ram intakes allowed.

Fuel systems must have shut off device within reach of the driver, marked in large bold block letters and "Day glow-Red" color for easy identification. A Waterman Shut-off system is recommended for additional safety.

All fuel lines and filters will be securely and safely mounted to the satisfaction of the officials. NO EXCEPTION

5.14 Ignition

Any ignition system or magneto allowed.

Cars must have a clearly marked ON/OFF ignition switch within reach of the driver and visible to rescue workers.

5.15 Starter

On board, working starters are REQUIRED.

5.16 Cooling System

No antifreeze is to be used at any time. Water and Water Wetter or equivalent ok.

6 Drivetrain

6.1 Bellhousing

Steel or approved aluminum shield that covers the flywheel mandatory when bell housing is inside the cockpit.

6.2 Clutch

6.3 Transmission

6.4 Flywheel

6.5 Driveshaft

All drive trains must have a driveline or rear end coupler system (to disengage rear end from engine).

PETALUMA SPEEDWAY

2016 Wingless Sprint Car Rules

Torque drive lines not allowed. All drivelines must be enclosed and have no more than 1 u-joint and that u-joint must be front of the drive line.

Buckley Yokes OK.

Torque tube safety strap or hoop mandatory.

6.6 Rear End

Any conventional quick change rear end is allowed with a maximum 2" offset.

6.7 Miscellaneous

7 Exhaust

7.1 Manifold/Header

7.2 Exhaust System

7.3 Mufflers

Mufflers are required. Mandatory 95dba @100 ft.

8 Body

8.1 Body, Body Types

Body must be mounted to the centerline of the chassis.

Body/chassis must be well maintained. NO JUNK. PAINT OVER RUSTED HEADERS ETC.

Conventional sprint car hoods allowed. Conventional side panels and tail tanks only.

NO AERODYNAMIC DEVICES ALLOWED. NO WINGS, WEDGES, FOILS, MODIFIED BELLY PANS (flat 0 UNDERSIDE MODIFICATIONS. NO EXCEPTIONS. THE OFFICIAL DECISION WILL BE FINAL. No body part designed to trap air or otherwise form a wind break except those to cool or protect the engine or braking system

Right side arm guard may not exceed 36" in height measured from top of bottom frame rail.

Driver must be able to easily escape the car. Drivers will be asked to demonstrate this capability.

Firewall will be solid metal and fit between the engine and the driver. Access holes may be drilled for wiring & linkage.

Floor pan must extend from the firewall to the front of the driver's seat.

8.2 Spoiler

8.3 Body Appearance

All cars will be painted in bright colors. All cars must meet the approval of the officials as to appearance.

8.4 Identification

NUMBERS WILL BE IN ACCORDANCE TO THE REGULATIONS OR NO PAY OR POINTS to be issued for the program.

Numbers must be contrasting and LARGE ENOUGH TO BE EASILY READ FROM THE SCORING BOOTH. NO EXCEPTIONS.

PETALUMA SPEEDWAY

2016 Wingless Sprint Car Rules

9 Fuel System

9.1 Fuel

RACING alcohol or gas only. No Nitro or Nitrous Oxide

NO ADDITIVES. Including oxygenated additives

No electric fuel pumps.

9.2 Fuel Cell

Fuel tank must be mounted to the centerline of the chassis.

A securely mounted fuel cell with bladder is required. Midget or sprint type is OK.

Minimum 25 Gallon tank. Maximum of 40 Gallons.

Fuel tanks may not be mounted to the chassis utilizing any portion of the access plate or the nut plates that bond the fuel bladder.

Mounting fuel tank to chassis: All mounting points must have inner and outer plates attached to the shell. They must be of adequate size to insure the tank is secure to the chassis. All tanks will have four different cage mounting points.

Tank vent MUST have check valve.

10 Tires and Wheels

10.1 Tires

Any compound Hoosier tire may be used.

10.2 Wheels

Any aluminum, or steel six-pin or spline wheel OK.

Any wheel offset is allowed.

Maximum wheel width: Front 10", Left Rear 15", Right Rear 18".

Bead locks on all wheels recommended.

11 Miscellaneous Class Specific Rules

Cars must start each event from staging WITHOUT ASSISTANCE. Cars requiring assistance at initial start of heat race or dash: go to the back of the pack. Cars requiring assistance at the initial start of a semi main or main event will be penalized eight positions. No penalty for requiring assistance during caution or red flag restart.

Any car or driver following a roll over will not be allowed to participate in any event that night, unless cleared through the official. Any official may make comments in regards to the condition of the car and/or driver.

12 Disclaimer

FROM: THE MANAGEMENT OF PETALUMA SPEEDWAY

The rules and/or regulations set forth herein are designed to provide for the orderly conduct of racing events and to establish minimum acceptable requirements for such events. These rules shall govern the condition of all events, and by participating in these events, all participants are deemed to have complied with these rules. NO EXPRESS OR IMPLIED WARRANTY OF SAFETY SHALL RESULT FROM PUBLICATION OF OR COMPLIANCE

PETALUMA SPEEDWAY

2016 Wingless Sprint Car Rules

WITH THESE RULES AND/OR REGULATIONS. They are intended as a guide for the conduct of the sport and are in no way a guarantee against injury or death to a participant, spectator or official. The race director shall be empowered to permit minor deviations from any of the specifications herein or impose any further restrictions that in his opinion do not alter the minimum acceptable requirements. NO EXPRESSED OR IMPLIED WARRANTY OF SAFETY SHALL RESULT FROM SUCH ALTERATION OF SPECIFICATIONS. Any interpretation or deviation of these rules is left to the discretion of the officials. Their decision is final. REFEREE'S DECISION IS FINAL.

2004 STATE RULES ALLOW NO LIQUID DUMPING FACILITIES AT THE FAIRGROUNDS. Each race car that enters the Fairgrounds Pit Area MUST have an empty container(s) approved by the MANAGEMENT OF PETALUMA SPEEDWAY that will hold at least 2 gallons of used oil (fluids) for collecting anything that may be drained out of the race car or tow vehicle at each event. These container(s) must be removed with the racecar after every race and be disposed of at an approved facility at the owner's expense.

IMPORTANT NOTICE

It is ultimately the obligation of each participant to insure that his/her conduct and equipment comply with all applicable Petaluma Speedway rules and regulations as they may be amended from time to time. No expressed or implied warranty of safety shall result from publication of or compliance with these rules. They are intended as a guide for conduct of the sport and are in no way a guarantee against injury or death to